

# TEKSLIDE<sup>®</sup>

**HIGH PERFORMANCE**

FLUOROPOLYMER MATERIALS

low friction

high wear resistance

chemical resistance

low maintenance



YOUR CHOICE FOR  
**FLUOROBASED PRODUCTS**



**4200**  
tons. of PTFE materials processed every year

**350**  
people involved

**2100**  
regular customers

**58**  
supplied countries

**7**  
branche offices and companies



GUARNIFLON<sup>®</sup> was established in 1982, enthusiasm, dedication and perseverance being the key factors which have allowed the company to evolve to the present status of worldwide leader in PTFE and fluorochemicals business field.

During recent years GUARNIFLON<sup>®</sup> has lead an International Group of companies which are continually integrating with the foreign markets, utilising the most updated marketing, technological tools and management flair.

**TEKSLIDE** is the GUARNIFLON<sup>®</sup> Trade Mark for High Performance Fluoropolymer Materials, a special group of PTFE compounds, developed by GUARNIFLON<sup>®</sup> R&D and among the best solutions today offered for applications where lubrication could be a tough problem.

The materials of **TEKSLIDE** products offer the best combination of properties in terms of low coefficient of friction and high were resistance in a wide variety of operating situations.

# TEKSLIDE

## HIGH PERFORMANCE FLUOROPOLYMER MATERIALS

Beside the wide range of the existing **PTFE** products, GUARNIFLON® developed the **TEKSLIDE** products, **PTFE** compounded grades used in the processing of tapes, bearing tapes and machined parts retaining the usual and well known conventional **PTFE** advantages improved at the same time by some enhanced properties:

- **low coefficient of friction**
- **high resistance and hardness**
- **low cold flow**
- **extreme temperature applications**
- **very high pressure resistance**

GUARNIFLON® **TEKSLIDE** products can be supplied etched in order to allow the most performing applications in the mechanical and other tribological fields.

Special compounds not included in this catalogue available on request.

### TRIBOLOGICAL PROPERTIES

- Excellent performance in dry conditions at high PV values, the product of operating pressure and surface velocity. The PV value in dry conditions ( max 1.7 MPa x M/S ) can be widely overcome in case of lubricated applications
- Extremely low coefficient of friction static and dynamic
- Extremely low stick-slip effect
- Excellent wear resistance even in dry applications

### THERMAL PROPERTIES

- Stable behavior at operating temperatures from -240° C to +260° C and for short time up to +280° C
- Dimensional stability
- Excellent thermal dissipation capacity ( specific grades )

### CHEMICAL PROPERTIES

- Excellent chemical inertness
- **TEKSLIDE** materials can operate in salt water, in steam environment or aggressive and corrosive chemical environments
- Good gas proof properties (specific grades)

### ELECTRICAL PROPERTIES

According to different grades of **TEKSLIDE** materials the following properties can be enhanced:

- Good dielectric properties (insulation)
- Excellent conductivity properties for antistatic applications

### MECHANICAL PROPERTIES

- Extremely high PV and sliding behavior
- High load compression resistance (radial/axial)
- Low abrasive surface for applications on soft countersurfaces
- Excellent vibration dampening and noiseless

### OTHER TYPICAL PROPERTIES

- Flexibility and fatigue stress resistance
- Some of the **TEKSLIDE** materials are atoxic and excellent for food contact and food industry applications

## AVAILABLE MATERIALS

TEKSLIDE **G471**  
dark Red

TEKSLIDE **G461**  
yellow

TEKSLIDE **G729**  
white

TEKSLIDE **G453**  
black

TEKSLIDE **G412**  
dark grey

TEKSLIDE **G418**  
grey/blue

TEKSLIDE **G479**  
light brown

TEKSLIDE **G464 | G488 | G417 | G548**  
green/blue

TEKSLIDE **G416 | G506 | G458**  
brown

## AVAILABLE TECHNOLOGIES

**AUTOMATIC MOULDING**  
custom bearings

**COMPRESSION MOULDING**  
components, rods, tubes and sheets

**EXTRUSION**  
rods and tubes

**SKIVING**  
tapes and films

**MACHINING**  
CNC and automatic turning custom made parts

**PRESSURE/SINTERING MOULDING**  
billets for high performance tapes and films

# MATERIALS SELECTION GUIDE

PRODUCTS	G471	G461	G729	G453	G412	G418	G479	G464 G488 G417 G548	G416	G506	G458
Color	DarkRed	Yellow	White	Black	DarkGrey	Grey Blue	Light Brown	Green	Brown	Brown	Brown
Max Load "P" (psi)	1,000	750	1,000	1,000	1,000	1,000	1,200	1,000	1,000	1,200	1,200
MPa	6.9	5.2	6.9	6.9	6.9	6.9	8.3	6.9	6.9	8.3	8.3
Max Speed "V" (fpm)	400	400	400	400	400	400	400	400	400	400	400
m/s	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0
Max "PV" (psi-fpm)	10,000	7,500	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000
(MPa•m/s)	0,35	0,26	0,35	0,35	0,35	0,35	0,35	0,35	0,35	0,35	0,35
Rb 25 & higher		X	X	X	X	X	X				
Rc 35 & higher	X							X	X	X	X
Painted metal and porcelain						X					
Aluminium		X					X				
Steam	X		X	X	X	X	X	X	X	X	X
Wet	X		X	X	X	X	X	X	X	X	X
Dry	X	X	X	X	X	X	X	X	X	X	X
Vacuum	X	X	X				X	X	X	X	X
Coefficient of friction	4	1	1	2	2	3	1	2	2	2	2
Creep resistance	4	3	4	4	4	4	4	5	5	5	5
Insulative prop.	YES	YES	YES	NO	NO	YES	YES	NO	NO	NO	NO

**G471** | Our standard **TEKSLIDE** bearing grade. Higt Creep and Abrasion resistance.

**G461** | Lowest Coefficient of friction of **TEKSLIDE** series. Excellent insulator.

**G729** | Widely used in the food process industry.

**G453** | Very good operation in wet environments.

**G412** | Good thermal and electrostatic dissipation.

**G418** | Excellent abrasion resistance.

**G479** | The best **TEKSLIDE** against alluminium surfaces.

**G464**  
**G488**  
**G417**  
**G548** | Extensively used machine tool guide ways.

**G416** | Guide ways and piston rings

**G506** | Guide ways

**G458** | Piston Rings



## **Bearing Tapes**

All kinds of bearings are available in standard materials as well as G471, G461 and G464, for the heaviest applications in the hydraulic, motion control and mechanical fields. They're made by special PTFE compounds and technologies, in order to fulfil GUARNIFLON®'s customers' requirements.

Special fillers are selected to enhance properties such as:

- wear resistance
- coefficient of friction
- compression strength

Thickness from mm. 1,5 to mm. 5

Width from mm. 4 to mm. 300

## **Rings**

Whenever the chemical and thermal resistance of standard rings in static applications like static seals or flange connections is no longer sufficient, PTFE rings are the solution. Standard dimensions as well as special dimensions under customer specifications are available.

## **Tapes**

Most materials can be skived thanks to the technologies available nowadays in GUARNIFLON® up to mm. 6 according to customers' needs.

TEKSLIDE tapes show excellent performance for applications where friction reduction is required.

## **Machined Products**

Automatic turning machines as well as CNC machines can produce more than 1.5 million pieces per day. To ensure high and stable quality standards, GUARNIFLON® is running the electronic system S.P.C. (Statistical Process Control).


## **Etching Technology for Bounding Purposes**

Guarniflon owns the most updated technologies dedicated to the etching process on semifinished and finished products.

The etching process of GUARNIFLON® is capable of providing uniform reactive surfaces.

# DRY COEFFICIENT OF FRICTION - STATIC

## ASTM D3702



**G471** | MIN 0.08 - MAX 0.20  
**G461** | MIN 0.05 - MAX 0.15  
**G729** | MIN 0.10 - MAX 0.20  
**G453** | MIN 0.06 - MAX 0.18  
**G412** | MIN 0.05 - MAX 0.15  
**G418** | MIN 0.10 - MAX 0.20  
**G479** | MIN 0.05 - MAX 0.15


**G464** | MIN 0.07 - MAX 0.18  
**G488** | MIN 0.07 - MAX 0.18  
**G417** | MIN 0.07 - MAX 0.18  
**G548** | MIN 0.07 - MAX 0.18  
**G416** | MIN 0.07 - MAX 0.20  
**G506** | MIN 0.10 - MAX 0.20  
**G458** | MIN 0.10 - MAX 0.25

### Note:

The values relevant to the dry coefficient of friction have to be considered as merely indicative, suitable only for a comparison of materials in the same operating conditions. They depend and are strongly influenced by the loads applied, speed, operating temperature, the environment conditions, the type of mated materials, the surface finish of the counterparts.

# DRY COEFFICIENT OF FRICTION - DYNAMIC

## ASTM D3702



**G471** | MIN 0.05 - MAX 0.20  
**G461** | MIN 0.10 - MAX 0.20  
**G729** | MIN 0.15 - MAX 0.23  
**G453** | MIN 0.12 - MAX 0.25  
**G412** | MIN 0.07 - MAX 0.15  
**G418** | MIN 0.08 - MAX 0.18  
**G479** | MIN 0.10 - MAX 0.20

**G464** | MIN 0.15 - MAX 0.25  
**G488** | MIN 0.15 - MAX 0.25  
**G417** | MIN 0.15 - MAX 0.25  
**G548** | MIN 0.15 - MAX 0.25  
**G416** | MIN 0.15 - MAX 0.25  
**G506** | MIN 0.15 - MAX 0.25  
**G458** | MIN 0.15 - MAX 0.30

**Note:**


The values relevant to the dry coefficient of friction have to be considered as merely indicative, suitable only for a comparison of materials in the same operating conditions. They depend and are strongly influenced by the loads applied, speed, operating temperature, the environment conditions, the type of mated materials, the surface finish of the counterparts.

# DEFORMATION UNDER LOAD MAX TYPICAL VALUE

Room temperature 24 hours at 13.7 N/mm<sup>2</sup>  
ASTM D621


Max Typical Value %

G471	9
G461	8
G729	14
G453	7
G412	10
G418	8
G479	13
G464	8
G488	8
G417	8
G548	8
G416	8
G506	6,5
G458	6



## WEAR RATE COMPARISON AT PV 0,7


TEKSLIDE MATERIALS VS. TRADITIONAL PTFE



pv 0,7= 0,7 N/mm<sup>2</sup> x 1 m/s

# COMPRESSIVE STRENGTH MIN. TYPICAL VALUE


At 1% Deformation  
ASTM D695



Min. Typical Value	
G471	8
G461	6
G729	5
G453	7
G412	6,5
G418	8
G479	7
G464	8
G488	8
G417	8
G548	8
G416	8
G506	8
G458	10

## COMPARISON OF COMPRESSIVE LOAD

VS. DEFORMATION OF SOME TEKSLIDE GRADES





PRODUCTS



# TEKSLIDEG471



General purpose dry bearing material for bushing and sliding pads for mechanical applications in general. Slide ways for machine tools.

High wear and abrasion resistance, good compressive properties. Suitable for the majority of dry bearing applications against hard counter-surfaces. Good electrical insulating properties.

## PRODUCTS

Moulded tubes  
Moulded rods  
Moulded sheets  
Extruded tubes  
Extruded rods  
Skived tapes  
Machined parts  
Piston rings  
Bearing tapes

## APPLICATIONS

Compressors  
Pumps  
Wear bands  
Automotive  
Insulators  
Linear Slides

## TECHNICAL DATA SHEET TEKSLIDE G471

Properties	Unit	Method	Moulded
<b>PHYSICAL - MECHANICAL</b>			
Density	g/cm <sup>3</sup>	ASTM D792	2,20 - 2,30
Hardness - Shore D	/	ASTM D2240	≥ 60
Tensile strength CD	N/mm <sup>2</sup>	ASTM D4745	≥ 14
Elongation at break CD	%	ASTM D4745	≥ 170
Compressive strength at 1% deformation	N/mm <sup>2</sup>	ASTM D695	≥ 8
Deformation under load at room temperature 24hours at 13,7 N/mm <sup>2</sup>	%	ASTM D621	≤ 9
Permanent deformation as above after releasing of 24 hours at room temperature	%	ASTM D621	≤ 4
Dynamic Coefficient of friction ( PV = 0,7 N/mm <sup>2</sup> •m/s)	/	ASTM D3702	0,05 - 0,20
Wear factor ( PV = 0,7 N/mm <sup>2</sup> •m/s)	µm/h•N/mm <sup>2</sup> •m•min	ASTM D3702	0,010 - 0,020
<b>THERMAL</b>			
Service Temperature (min-max)	°C	/	- 200 / + 260
Thermal expansion coefficient (linear) 25 - 100°C	10 <sup>-5</sup> /°C	ASTM D696	9 - 11

# TEKSLIDE G461



The lowest coefficient of friction in dry applications. Suitable for the machining of bearings and other sliding parts for the food industry or for any other use in contact with soft materials such as aluminium, copper alloys, inox steel, polymeric substrates, etc. Very good wear resistance, compression resistance, high flexibility and tensile strength, excellent insulating properties. It can be used in contact with food products.

## PRODUCTS

Moulded tubes  
Moulded rods  
Moulded sheets  
Skived tapes  
Machined parts  
Piston rings  
Bearing tapes

## APPLICATIONS

Air Compressors  
Wear bands  
Automotive  
Insulators  
Linear Slides  
Mechanical textile

## TECHNICAL DATA SHEET TEKSLIDE G461

Properties	Unit	Method	Moulded
<b>PHYSICAL - MECHANICAL</b>			
Density	g/cm <sup>3</sup>	ASTM D792	1,85 - 2,05
Hardness - Shore D	/	ASTM D2240	≥ 55
Tensile strength CD	N/mm <sup>2</sup>	ASTM D4745	≥ 15
Elongation at break	%	ASTM D4745	≥ 250
Compressive strength at 1% deformation	N/mm <sup>2</sup>	ASTM D695	≥ 6
Deformation under load at room temperature 24hours at 13,7 N/mm <sup>2</sup>	%	ASTM D621	≤ 8
Permanent deformation as above after releasing of 24 hours at room temperature	%	ASTM D621	≤ 6
Dynamic Coefficient of friction ( PV = 0,7 N/mm <sup>2</sup> •m/s)	/	ASTM D3702	0,10 - 0,20
Wear factor ( PV = 0,7 N/mm <sup>2</sup> •m/s)	µm/h•N/mm <sup>2</sup> •m•min	ASTM D3702	0,010 - 0,020
<b>THERMAL</b>			
Service Temperature (min-max)	°C	/	- 200 / + 260
Thermal expansion coefficient (linear) 25 - 100°C	10 <sup>-5</sup> /°C	ASTM D696	9 - 11

# TEKSLIDE G729



Its excellent load and wear characteristics together with the capability to stand a wide range of temperatures, make Tekslide G729 the perfect material for bearings for food and pharmaceutical applications.

High compatibility with a wide range of mating surfaces.

Tekslide G729 is unaffected by all common acids, bases and solvents.

## PRODUCTS

Moulded tubes  
Moulded rods  
Extruded tubes  
Extruded rods  
Skived tapes  
Machined parts  
Piston rings  
Seals

## APPLICATIONS

Compressors  
Pumps  
Insulators  
Wear bands  
Automotive  
Linear Slides

## TECHNICAL DATA SHEET TEKSLIDE G729

Properties	Unit	Method	Moulded
<b>PHYSICAL - MECHANICAL</b>			
Density	g/cm <sup>3</sup>	ASTM D792	2,17 - 2,25
Hardness - Shore D	/	ASTM D2240	≥ 55
Tensile strength CD	N/mm <sup>2</sup>	ASTM D4745	≥ 14
Elongation at break	%	ASTM D4745	≥ 200
Compressive strength at 1% deformation	N/mm <sup>2</sup>	ASTM D695	≥ 5
Deformation under load at room temperature 24hours at 13,7 N/mm <sup>2</sup>	%	ASTM D621	≤ 14
Permanent deformation as above after releasing of 24 hours at room temperature	%	ASTM D621	6 - 9
Dynamic Coefficient of friction ( PV = 0,7 N/mm <sup>2</sup> •m/s)	/	ASTM D3702	0,15 - 0,23
Wear factor ( PV = 0,7 N/mm <sup>2</sup> •m/s)	µm/h•N/mm <sup>2</sup> •m•min	ASTM D3702	0,015 - 0,023
<b>THERMAL</b>			
Service Temperature (min-max)	°C	/	- 200 / + 260
Thermal expansion coefficient (linear) 25 - 100°C	10 <sup>-5</sup> /°C	ASTM D696	7 - 10

# TEKSLIDE G453



For bearing and sliding parts. Piston bearer rings for no-lubricated reciprocating compressors and for automotive applications.

Very good load carrying properties combined with low friction and high wear resistance. Good thermal and electrostatic dissipation.

Suitable for wet operating conditions and for contact with corrosive agents.

## PRODUCTS

Moulded tubes  
Moulded rods  
Moulded sheets  
Extruded tubes  
Extruded rods  
Skived tapes  
Machined parts  
Piston rings  
Bearing tapes  
Cup seals

## APPLICATIONS

Compressors  
Pumps  
Wear bands  
Automotive  
Linear Slides  
Plating tanks  
Valve seats

## TECHNICAL DATA SHEET TEKSLIDE G453

Properties	Unit	Method	Moulded
<b>PHYSICAL - MECHANICAL</b>			
Density	g/cm <sup>3</sup>	ASTM D792	2,05 - 2,11
Hardness - Shore D	/	ASTM D2240	≥ 60
Tensile strength CD	N/mm <sup>2</sup>	ASTM D4745	≥ 13
Elongation at break	%	ASTM D4745	≥ 70
Compressive strength at 1% deformation	N/mm <sup>2</sup>	ASTM D695	≥ 7
Deformation under load at room temperature 24hours at 13,7 N/mm <sup>2</sup>	%	ASTM D621	≤ 7
Permanent deformaton as above after releasing of 24 hours at room temeperature	%	ASTM D621	≤ 5
Dynamic Coefficient of friction ( PV = 0,7 N/mm <sup>2</sup> •m/s)	/	ASTM D3702	0,12 - 0,25
Wear factor ( PV = 0,7 N/mm <sup>2</sup> •m/s)	µm/h•N/mm <sup>2</sup> •m•min	ASTM D3702	0,010 - 0,020
<b>THERMAL</b>			
Service Temperature (min-max)	°C	/	- 200 / + 260
Thermal expansion coefficient (linear) 25 - 100°C	10 <sup>-5</sup> /°C	ASTM D696	10 - 12

# TEKSLIDEG412



Non-abrasive PTFE compound for softer mating surfaces, such as stainless steel.

High resistance to deformation, extremely low coefficient of friction and good thermal and electrostatic dissipation. Use in water reduces the wear rate.

Not suggested for using in ultra-dry, vacuum applications, or where electrical insulation is desired.

## PRODUCTS

Moulded tubes  
Moulded rods  
Moulded sheets  
Extruded tubes  
Extruded rods  
Skived tapes  
Machined parts  
Piston rings  
Bearing tapes

## APPLICATIONS

Compressors  
Pumps  
Automotive-Lip seals  
Linear Slides

## TECHNICAL DATA SHEET TEKSLIDE G412

Properties	Unit	Method	Moulded
<b>PHYSICAL - MECHANICAL</b>			
Density	g/cm <sup>3</sup>	ASTM D792	2,10 - 2,15
Hardness - Shore D	/	ASTM D2240	≥ 55
Tensile strength CD	N/mm <sup>2</sup>	ASTM D4745	≥ 15
Elongation at break	%	ASTM D4745	≥ 170
Compressive strength at 1% deformation	N/mm <sup>2</sup>	ASTM D695	≥ 6,5
Deformation under load at room temperature 24hours at 13,7 N/mm <sup>2</sup>	%	ASTM D621	≤ 10
Permanent deformaton as above after releasing of 24 hours at room temeperature	%	ASTM D621	≤ 6
Dynamic Coefficient of friction ( PV = 0,7 N/mm <sup>2</sup> •m/s)	/	ASTM D3702	0,07 - 0,15
Wear factor ( PV = 0,7 N/mm <sup>2</sup> •m/s)	µm/h•N/mm <sup>2</sup> •m•min	ASTM D3702	0,015 - 0,025
<b>THERMAL</b>			
Service Temperature (min-max)	°C	/	- 200 / + 260
Thermal expansion coefficient (linear) 25 - 100°C	10 <sup>-5</sup> /°C	ASTM D696	12 - 13

# TEKSLIDEG418



The appropriate choice for applications in hydrogen and natural gas compressors, thanks to its excellent wear resistance, especially in extremely dry environments.

Its almost universal chemical resistance enables it to withstand corrosives and acids sometimes present in trace amounts in these environments.

## PRODUCTS

Moulded tubes  
Moulded rods  
Moulded sheets  
Extruded tubes  
Extruded rods  
Skived tapes  
Machined parts  
Piston rings  
Bearing tapes

## APPLICATIONS

Compressors  
Pumps  
Wear bands  
Automotive  
Linear Slides  
Insulators

## TECHNICAL DATA SHEET TEKSLIDE G418

Properties	Unit	Method	Moulded
<b>PHYSICAL - MECHANICAL</b>			
Density	g/cm <sup>3</sup>	ASTM D792	2,20-2,30
Hardness - Shore D	/	ASTM D2240	≥ 55
Tensile strength CD	N/mm <sup>2</sup>	ASTM D4745	≥ 15
Elongation at break	%	ASTM D4745	≥ 200
Compressive strength at 1% deformation	N/mm <sup>2</sup>	ASTM D695	≥ 8
Deformation under load at room temperature 24hours at 13,7 N/mm <sup>2</sup>	%	ASTM D621	≤ 8
Permanent deformaton as above after releasing of 24 hours at room temeperature	%	ASTM D621	≤ 4
Dynamic Coefficient of friction ( PV = 0,7 N/mm <sup>2</sup> •m/s)	/	ASTM D3702	0,08 - 0,18
Wear factor ( PV = 0,7 N/mm <sup>2</sup> •m/s)	µm/h•N/mm <sup>2</sup> •m•min	ASTM D3702	0,015 - 0,021
<b>THERMAL</b>			
Service Temperature (min-max)	°C	/	- 200 / + 260
Thermal expansion coefficient (linear) 25 - 100°C	10 <sup>-5</sup> /°C	ASTM D696	9 - 12

# TEKSLIDEG479



It combines low deformation under load with extremely good chemical resistance. Particularly suitable for operating against aluminium substrates, stainless steel, bronze, polymeric substrates. Composition based on ingredients approved for food contact, in accordance with the EEC regulations, self-lubricating properties (no lubrication needed), high wear resistance, load carrying capabilities, no relative abrasiveness, outstanding chemical resistance, very wide range of operating temperatures (from -200°C up to + 260°C). Very low coefficient of friction. Not recommended for use with alkalis.

## PRODUCTS

Moulded tubes  
Moulded rods  
Moulded sheets  
Skived tapes  
Machined parts  
Piston rings  
Bearing tapes

## APPLICATIONS

Air Compressors  
Automotive  
Insulators  
Linear Slides  
Mechanical textile  
Food processing machines  
Cosmetic machines  
Blistering machines

## TECHNICAL DATA SHEET TEKSLIDE G479

Properties	Unit	Method	Moulded
<b>PHYSICAL - MECHANICAL</b>			
Density	g/cm <sup>3</sup>	ASTM D792	1,92 - 2,06
Hardness - Shore D	/	ASTM D2240	≥ 55
Tensile strength CD	N/mm <sup>2</sup>	ASTM D4745	≥ 14
Elongation at break CD	%	ASTM D4745	≥ 220
Compressive strength at 1% deformation	N/mm <sup>2</sup>	ASTM D695	≥ 7
Deformation under load at room temperature 24hours at 13,7 N/mm <sup>2</sup>	%	ASTM D621	≤13
Permanent deformation as above after releasing of 24 hours at room temperature	%	ASTM D621	≤9
Dynamic Coefficient of friction ( PV = 0,7 N/mm <sup>2</sup> •m/s)	/	ASTM D3702	0,10 - 0,20
Wear factor ( PV = 0,7 N/mm <sup>2</sup> •m/s)	µm/h•N/mm <sup>2</sup> •m•min	ASTM D3702	0,011 - 0,018
<b>THERMAL</b>			
Service Temperature (min-max)	°C	/	- 200 / + 260
Thermal expansion coefficient (linear) 25 - 100°C	10 <sup>-5</sup> /°C	ASTM D696	9 - 12

# TEKSLIDE G464 - G488 - G417 - G548

BRONZE FILLED COMPOUNDS



TEKSLIDE brand has a various range of bronze filled PTFE compounds, each having a unique blend of additional components (inorganic ingredients) produced in accordance to specific market requirements.

Special fillers to satisfy the most arduous applications and available in a wide choice of colors, such as brown, dark green, light green and blue.

Excellent mechanical properties, perfect for machine tool applications.

Engineered compounds developed for use in linear bearing elements and to avoid metal-to-metal sliding contacts. Self lubricating, wear resistant materials providing low friction, stick-slip free operation, better positioning accuracy and repeatability, vibration dampening, long life with minimum wear.

They are dimensionally stable, maintenance free and can be operated with or without lubrication.

G464

G488

G417

G548

## TECHNICAL DATA SHEET TEKSLIDE G464 - G488 - G417 - G548

Properties	Unit	Method	Moulded
<b>PHYSICAL - MECHANICAL</b>			
Density	g/cm <sup>3</sup>	ASTM D792	3,00 - 3,20
Hardness - Shore D	Points	ASTM D2240	≥ 58
Tensile strength CD	N/mm <sup>2</sup>	ASTM D4745	≥ 20
Elongation at break CD	%	ASTM D4745	≥ 250
Compressive strength at 1% deformation	N/mm <sup>2</sup>	ASTM D695	≥ 8
Deformation under load at room temperature 24 hours at 13,7 N/mm <sup>2</sup> CD	%	ASTM D621	<8
Permanent deformation as above after releasing of 24 hours at room temperature CD	%	ASTM D621	<4
Dynamic Coefficient of friction ( PV = 0,7 N/mm <sup>2</sup> •m/s)	/	ASTM D3702	0,15 - 0,25
Wear factor ( PV = 0,7 N/mm <sup>2</sup> •m/s)	µm/h•N/mm <sup>2</sup> •m•min	ASTM D3702	0,010 - 0,030

### PRODUCTS

Moulded tubes  
Moulded rods  
Moulded sheets  
Extruded tubes  
Extruded rods  
Skived tapes  
Machined parts  
Piston rings  
Bearing tapes

### APPLICATIONS

Compressors  
Pumps  
Automotive  
Linear Slides  
Wear bands  
Insulators  
Machine Tools

### THERMAL

Service Temperature (min-max)	°C	/	- 200 / + 260
Thermal expansion coefficient (linear) 25 - 100°C	10 <sup>-5</sup> /°C	ASTM D696	8 - 10

# TEKSLIDEG416 - G506 - G458

BRONZE FILLED COMPOUNDS

The 3 additional Tekslide materials belonging to the PTFE bronze compounds group have technical behavioural differences according to the below data sheets.

Specific fillers to satisfy the heaviest applications, excellent mechanical properties, perfect for machine tool applications. Engineered compounds developed for use in linear bearing element and to avoid metal-to-metal sliding contacts. Self lubricating, wear resistant materials providing low friction, stick-slip free operation, better positioning accuracy and repeatability, vibration dampening, long life with minimum wear.

They are dimensionally stable, maintenance free and can be operated with or without lubrication.

## PRODUCTS

Moulded tubes  
Moulded rods  
Moulded sheets  
Extruded tubes  
Extruded rods  
Skived tapes  
Machined parts  
Piston rings  
Bearing tapes

## APPLICATIONS

Compressors  
Pumps  
Automotive  
Linear Slides  
Wear bands  
Insulators  
Machine Tools



## TECHNICAL DATA SHEET TEKSLIDE G416 - G506 - G458

## TEKSLIDE G416

Properties	Unit	Method	Moulded
<b>PHYSICAL - MECHANICAL</b>			
Density	g/cm <sup>3</sup>	ASTM D792	2,98 - 3,16
Hardness - Shore D	/	ASTM D2240	≥ 58
Tensile strength CD	N/mm <sup>2</sup>	ASTM D4745	≥ 18
Elongation at break CD	%	ASTM D4745	≥ 200
Compressive strength at 1% deformation	N/mm <sup>2</sup>	ASTM D695	≥ 8
Deformation under load at room temperature 24hours at 13,7 N/mm <sup>2</sup>	%	ASTM D621	≤ 8
Permanent deformation as above after releasing of 24 hours at room temperature	%	ASTM D621	≤ 5
Dynamic Coefficient of friction ( PV = 0,7 N/mm <sup>2</sup> • m/s)	/	ASTM D3702	0,15 - 0,25
Wear factor ( PV = 0,7 N/mm <sup>2</sup> • m/s)	µm/h•N/mm <sup>2</sup> • m•min	ASTM D3702	0,010 - 0,030
<b>THERMAL</b>			
Service Temperature (min-max)	°C	/	- 200 / + 260
Thermal expansion coefficient (linear) 25 - 100°C	10 <sup>-5</sup> /°C	ASTM D696	8 - 11



### TEKSLIDE G506

### TEKSLIDE G458

Unit	Method	Moulded
g/cm <sup>3</sup>	ASTM D792	3,41 - 3,61
/	ASTM D2240	≥ 60
N/mm <sup>2</sup>	ASTM D4745	≥ 15
%	ASTM D4745	≥ 200
N/mm <sup>2</sup>	ASTM D695	≥ 8
%	ASTM D621	≤6,5
%	ASTM D621	≤3
/	ASTM D3702	0,15 - 0,25
μm/h•N/mm <sup>2</sup> •m•min	ASTM D3702	0,010 - 0,030
°C	/	- 200 / + 260
10 <sup>-5</sup> /°C	ASTM D696	7 - 9

Unit	Method	Moulded
g/cm <sup>3</sup>	ASTM D792	3,75 - 3,95
/	ASTM D2240	≥ 62
N/mm <sup>2</sup>	ASTM D4745	≥ 15
%	ASTM D4745	≥ 100
N/mm <sup>2</sup>	ASTM D695	≥ 10
%	ASTM D621	≤6
%	ASTM D621	≤2,5
/	ASTM D3702	0,15 - 0,30
μm/h•N/mm <sup>2</sup> •m•min	ASTM D3702	0,010 - 0,030
°C	/	- 200 / + 260
10 <sup>-5</sup> /°C	ASTM D696	7 - 8

# QUALITY MANAGEMENT R&D TEAM



Guarniflon have been Quality Certified since 1993, certificate n. 015, one of the first in its own field.

**Nowadays Guarniflon is UNI EN ISO 9001 certified by the certification body Cermet.**

Guarniflon policy implies a high powered and experienced R & D Team continuously improving and developing day by day new solutions for new applications.

**SINCERT**



**CSI**  
**FOOD PACKAGING MATERIALS LABORATORIO**  
**RAPPORTO DI PROVA**  
**Test Report**  
 N° 0219/FPM/FDC09\_4 R  
**PTFE G508 Plate**  
**GUARNIFLON SPA**  
 VIA T. TASSO, 12  
 24060 TAGLIANO DI CASTELLI CALEPIO (BG)  
**GUARNIFLON SPA**  
 Big Nocerà  
 Copy to Division Head



Our Ref. CRUJC  
 1 September 2006

Guarniflon Spa  
 Tasso 12  
 Tagliano Di Castello (BG)

Technologiezentrum Wasser (TZW)  
 Karlsruhe  
 Prüfstelle Wasser

**TZW**

**WRAS**  
 Water Regulations Advisory Scheme  
 IS (V)

KTW-Empfehlungen des Bundesgesundheitsamtes  
 1, ITALIA

**WE HAVE PASSED FULL TESTS OF EFFECT ON WATER QUALITY - BS 6920\***  
 application for the material(s) described below to be approved arising from the tests of effect on water quality that have been carried out on the product(s) so been decided that there is no objection to its/their use provided the following processing processes of the ingredients and products are not changed. (See...)

**PETHYLENE**

PTFE lube. For cold water and hot water use up to 85°C.

Materials which have passed full tests of effect on water quality. **GUARNIFLON SPA**  
 are included in this letter, namely that the product as listed, having a quality, as suitable for use in contact with potable water and is included in the Materials section, Part Two, of the Water Regulations Advisory Scheme - "Approved Product". Approval of this product does not signify typical properties for any use.  
 I reserves the right to review approval. This product assessment in August 2011.

ergesbenisse

4.-6. Tag	7.-9. Tag	Reichtwert für 3. Extraktion
n/b	n/b	nicht normenwert beeinflusst
<0,4	<0,4	≤ 0,0
<1	<1	≤ 7,5

2. Tag	3. Tag	Reichtwert für 3. Tag
n/b	n/b	< 4
2	2	≤ 60,0

G 400\* entsprechen den Anforderungen der KTW-Empfehlungen des BfG  
 \* 2. Mitt. BfG in Bereichs-Übersichten D1 und D2.

Dr. I. Wagner

andernfalls festgelegten Bestimmungen. Sie werden jedoch spätestens 6 Jahre nach

g oder in Ausfüllen - ist ohne auszweckliche Genehmigung von Seiten des Prüfabw. nicht gültig  
 am Wasser in eine Einrichtung der nicht aus Gas- und Wasserföhrung e.V.  
 Karlsruhe Straße 14  
 D-76133 Karlsruhe  
 Telefon +49(0)71 521 52 0  
 Telefax +49(0)71 521 50 0



www.GUARNIFLON.com

**TEKSLIDE**  
 HIGH PERFORMANCE FLUOROPOLYMER MATERIALS



## GUARNIFLON INTERNATIONAL NETWORK



**UK**  
**MACEPLAST**  
 PTFE FINISHED AND SEMIFINISHED PRODUCTS  
 MEMBER OF GUARNIFLON S.p.A.

**Maceplast U.K. Ltd.**  
**U.K.**  
 347 Moorside Road - Swinton - Manchester M27 9HH  
<http://www.maceplastuk.com> - [sales@maceplastuk.com](mailto:sales@maceplastuk.com)



**GERMANY**  
**MACEPLAST**  
 HALBZEUGE UND FERTIGTEILE AUS PTFE  
 MEMBER OF GUARNIFLON S.p.A.

**Maceplast GmbH**  
**Germany**  
 Neusser Str. 115-117 - 41363 Jüchen  
<http://www.maceplast.de> - [info@maceplast.de](mailto:info@maceplast.de)



**FRANCE**  
**MACEPLAST**  
 PRODUITS PTFE FINIS ET SEMI-FINIS  
 MEMBER OF GUARNIFLON S.p.A.

**Maceplast France S.A.**  
**France**  
 18/20 Rue Ampère - Z.I. 69680 Chassieu  
<http://www.maceplast.fr> - [info@maceplast.fr](mailto:info@maceplast.fr)



**ROMANIA**  
**MACEPLAST**  
 PRODUSE FINITE SI SEMIFINITE DIN PTFE  
 MEMBER OF GUARNIFLON S.p.A.

**Maceplast Romania S.A.**  
**Romania**  
 Str. Aurel Vlaicu Nr. 37 - Otopeni - Judet Ilfov  
<http://www.maceplast.ro> - [commercial@maceplast.ro](mailto:commercial@maceplast.ro)



**Guarniflon India Pvt. Ltd.**  
**India**  
 S. No. 116/1 and 116/2 Village Kala, Amboli,  
 Silvassa 396230, Dadra & Nagar  
 Haveli, Union Territory - India  
<http://www.guarniflon.in> - [info@guarniflon.in](mailto:info@guarniflon.in)



**IPM – Industrial Plastics & Machine Inc.**  
**U.S.A.**  
 6829 s. Choctaw drive - BatonRouge, LA 70806  
<http://www.indplastics.com> - [info@indplastics.com](mailto:info@indplastics.com)



**Guarniflon Guangzhou Representative Office**  
 Zhong 1122, Times Square, No.30  
 Tianhebeilu, Tianhe District,  
 Guangzhou, Guangdong  
 P. R. of China  
[luo@guarniflon.com](mailto:luo@guarniflon.com)

### HEADQUARTERS - GUARNIFLON S.P.A.

Via T. Tasso, 12  
 24060 - Tagliuno di Castelli Calepio  
 Bergamo - Italy  
 Tel. +39.035.4494311 - Fax +39.035.4494336  
[info@guarniflon.com](mailto:info@guarniflon.com)  
[www.guarniflon.com](http://www.guarniflon.com)





# YOUR CHOICE FOR FLUOROBASED PRODUCTS

**Guarniflon S.p.A.**

Via T. Tasso, 12  
24060 - Tagliuno di Castelli Calepio  
Bergamo - Italy  
Tel. +39.035.4494311  
Fax +39.035.4494336  
info@guarniflon.com  
www.guarniflon.com  
GPS: N45°38.2605, E009°53.5665

**INTERNATIONAL SALES**

sales@guarniflon.com  
Fax +39.035.4425238